

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

No. 250

1. Unique identification of the product-type:

"MARISEAL 250 / MARISEAL 250FLASH"

2. Intended use:

Liquid applied roof waterproofing kits based on polyurethane resin

3. Manufacturer:

MARIS POLYMERS SA Industrial Area of Inofita GR-32011 / Inofita

4. Authorized representative

Not relevant

5. System of AVCP:

System 3

6. European Assessment Document: Guideline for European technical approval of "liquid applied roof waterproofing kits", ETAG 005 part 6: "specific stipulations for kits based in polyurethane", Version March 2000, Amended March 2004, used as European Assessment Document(EAD) according to article 66 Paragraph 3 of regulation(EU) Nº 305/2011.

European Technical Assessment: ETA-05/0197 of 7 April 2014

Technical Assessment Body: Deutsches Institut für Bautechnik
Notified Body: Materialprüfanstalt für das Bauwesen (MPA BS), (0761-CPD)

7. Declared performance:

ETAG 005 - part 6

Essential characteristics	Performance	System of AVCP
Water vapour resistance value in µ	1830	
Working life	W2 and W3	
Climatic zones	M and S	
Imposed loads	P1 to P4	-
Roof slope	S1 to S4	
Lowest surface temperature:	TL4	System 3
Highest surface temperature:	TH4	

Maris Polymers® POLYURETHANE SYSTEMS

Resistance to spreading fire and radiant heat:	NPD				
Reaction to fire:	Class E				
Statement on dangerous substances:	Does not contain any				
Resistance to wind loads	> 50 kPa	1			

NPD: No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kostas Varelas R&D Manager MARIS POLYMERS SA

MARIS POLYMERS

IND. AREA MOFYTAVIOTIA

WAT No EL 999528243

INOFITA, 22-03-2019