DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/20111 amended by Commissions delegated Regulation (EU) No 574/2014

No.9282

1. Unique identification code of the product-type: MARISEAL 282W

2. Intended use: Surface protection product for concrete – coating

Principles 1 Protection against Ingess - method 1.3

Principles 2 Moisture Control - method 2.2 Principles 8 Increasing Resistivity – method 8.2

3. Manufacturer: MARIS POLYMERS S.A.

Industrial Area of Inofita

GR-32011 Inofita

Greece

4. Authorised representative: Not relevant

5. System of assessment and verification of

constancy of performance:

System 4

6. Harmonised standard: EN 1504-2: 2004, ZA1.d, ZA1.e

Products and systems for the protection and repair of concrete structures. Definitions, requirements, quality control

and evaluation of conformity. Part 2: Surface protection

system for concrete

Notified body: Not relevant (see 5)

7. Declared performances:

Essential characteristics	Performance	Test standard	Harmonized technical specification
Linear shrinkage	NPD	EN 12617-1	EN 1504-2: 2004
Coefficient of thermal expansion	NPD	EN 1770	
Adhesion by cross-cut test	NPD	EN ISO 2409	
Permeability to CO ₂	S _D >50m	EN 1062-6	
Water vapour permeability	Class I: s _D < 5 m	EN ISO 7783	
Capillary absorption and permeability to water	ω < 0,1 kg/m².h ^{0,5}	EN 1062-3	
Thermal compatibility	NPD	EN 13687-1,2,3	
Crack bridging ability	NPD	EN 1062-7	
Adhesion strength by pull-off test	≥ 1,5 (1,0) 1) N/mm ²	EN 1542	
Reaction to fire	Class F	EN 13501-1	
Slip / skid resistance	NPD	EN 13036-4	
Behaviour after artificial weathering	NPD	EN 1062-11	
Antistatic behaviour	NPD	EN 1081	
Adhesion on wet concrete	NPD	EN 13578	
Dangerous substances	According 5.3	-	

Note: 1) The value in brackets is the lowest accepted value of any reading

The performance of the product identified above is in conformity with the set of declared performances. This

Inofyta, 30/11/2020 Dimitris Marinis Quality Responsible

Inofyta, 30/1/1/2020 Thomas Offreo Managing Director