

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/20111
amended by Commissions delegated Regulation (EU) No 574/2014
No 670

1. Unique identification code of the product-type: **MARISEAL 670**
2. Intended use: Liquid-applied water impermeable product, type RM for installations on walls and floors, beneath ceramic tiling (bonded with C2 adhesive in accordance with EN 12004)
3. Manufacturer: **MARIS POLYMERS S.A.
Industrial Area of Inofita
GR-32011 Inofita
Greece**
4. Authorised representative: Not relevant
5. System of assessment and verification of constancy of performance: **System 3**
6. Harmonised standard: **EN 14891: 2012/AC: 2013**
Liquid-applied water impermeable products for use beneath ceramic tiling bonded with adhesives - Requirements, test methods, evaluation of conformity, classification and designation.
- Notified body: **No. 1301**
TECHNICKÝ A SKÚŠOBNÝ ÚSTAV STAVEBNÝ, n. o.
Studená 3, 821 04 Bratislava, Slovak Republic

7. Declared performances:

Essential characteristics	Performance	Test standard	Harmonized technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	EN 14891, Clause A6.2	EN 14891: 2012 /AC: 2012
Waterproofing	No penetration	EN 14891, Clause A.7	
Crack bridging ability under standard conditions	$\geq 0,75 \text{ mm}$	EN 14891, Clause A.8.2	
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$	EN 14891, Clause A6.5	
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$	EN 14891, Clause A6.4	
Tensile adhesion strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$	EN 14891, Clause A6.9	
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	EN 14891, Clause A6.6	
Release dangerous substances	see MSDS	-	-

The performance of the product identified above is in conformity with the set of declared performances.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Maris Polymers S.A.

MARIS POLYMERS M.A.E
ΠΑΡΑΓΩΓΗ ΣΥΣΤΗΜΑΤΩΝ ΠΡΟΣΤΑΣΙΑΣ
ΘΕΣΗ ΡΟΥΜΑΝΙ - ΟΙΝΟΦΥΤΑ ΒΟΙΩΤΙΑΣ 3291
ΤΗΛ.: 226203281 / 22620310
Α.Φ.Μ. 999999999
R&D MANAGER