



MARISEAL • DETAIL[®]

ROOF DETAILS WATERPROOFING

Maris Polymers[®]
POLYURETHANE SYSTEMS

MARISEAL•DETAIL®

ROOF DETAILS WATERPROOFING


MARISEAL•DETAIL®

The **MARISEAL•DETAIL** is a liquid-applied, thixotropic, permanent elastic, **fiber-reinforced**, one component polyurethane coating used for long-lasting waterproofing of complex roofing details and connections.



The **MARISEAL•DETAIL** is mainly used to waterproof details like:

- Pipes
- Flashings and 90° angles
- Lightdomes
- Chimneys
- Photovoltaic systems
- Wall-floor connections
- Gutters, etc.



advantages

- simple application (brush)
- fiber reinforced
- it forms seamless membrane without joints or leak possibilities
- resistant to water, rain and frost
- maintains its mechanical properties over a temperature span of -30°C to +80°C
- provides water vapor permeability
- full surface adherence without any additional anchoring
- in case of damage, membrane can be easily repaired locally within minutes
- low cost



The ***MARISEAL-DETAIL SYSTEM*** consists of the compatible components:

- ***MARISEAL-DETAIL***
- ***MARISEAL-DETAIL REINIGER (CLEANER)***
- ***MARISEAL-DETAIL PRIMER***
- ***MARIFLEX-PU30 SEALANT***

The ***MARISEAL-DETAIL*** can be used on:



Beton



Mortar



Brick



Mineral finished bitumenfelt



Plain Bitumenfelt



PVC and EPDM membrane



Metal




PVC and Aluminium profile



Wood, etc

Connections and details treated properly

example 1: Lightdome



Mask the area to be waterproofed, with a masking tape in a sufficient size. Prepare the surface according to the surface preparation table.



Apply the first layer of MARISEAL DETAIL with a flat brush and spread evenly.



Apply the second layer of MARISEAL DETAIL thickly with a flat brush and remove masking tape.



If desired, for aesthetic reasons, slate chippings can be sprinkled in the wet coating in excess. Apply slight pressure by hand to stabilize the slate chippings.

example 2: Pipe Penetration



Mask the area to be waterproofed, with a masking tape in a sufficient size. Prepare the surface according to the surface preparation table.



Apply the first layer of MARISEAL DETAIL with a flat brush and spread evenly.



Apply the second layer of MARISEAL DETAIL thickly with a flat brush and remove masking tape.



If desired, for aesthetic reasons, slate chippings can be incorporated in the coating in excess.

Important

Surface preparation:		Primer not necessary	MARISEAL DETAIL PRIMER recommended
Polymeric Bitumenfelt (APP/SBS)	*5	x	
Chippings finished Bitumenfelt (APP/SBS)	*4	x	
Chippings finished Oxidized Bitumenfelt	*4	x	
Plain Oxidized Bitumenfelt	*5	x	
Painted surfaces	*3	x	
Steel	*1, *3	x	
Aluminium	*1, *3	x	
Copper	*1	x	
Zinc	*1	x	
Concrete	*2, *6		x
Lightweight concrete	*2, *6		x
Plaster	*2, *6		x
Screed	*2, *6		x
Brick	*2, *6		x
Stones	*2, *6		x
EPDM membranes	*1, *7	x	
PVC membranes	*1, *7	x	
PVC rigid	*1	x	
Wood	*2		x
Polyester	*1, *7	x	
Acrylic glass	*1	x	
Glass	*1	x	

*1: Before application, grind surface with sandpaper or grinding wheel. Then thoroughly clean/degrease with MARISEAL DETAIL CLEANER.
 *2: Residual moisture content of mineral substrates max. 5%. New cementitious surfaces must be at least 28 days old. Remove loose pieces mechanically.
 *3: Always remove old paints.
 *4: MARISEAL DETAIL PRIMER binds the slate chippings on the bitumenfelt. If in doubt it is recommended to use the MARISEAL DETAIL PRIMER.
 *5: Liquify surface by firetorch and immediately saturate with enough dry silica sand (0.4-0.8mm).
 *6: Before coating, brush off the surface with a wire brush, to roughen it.
 *7: Always perform adhesion test before application
 For not listed substrates please contact MARIS POLYMERS application department.

All information regarding the treatment of surfaces is to be considered indicative, as corresponds to the current level of laboratory and practical experience. Given the multitude of different materials in the market, deviations are possible. Therefore, absolute accuracy of given information can not be guaranteed. Due to the different object requests and the varying conditions, an adhesion test is necessary to guarantee suitability for the specific purpose. Preliminary coating adhesion tests are therefore recommended in all cases. Should doubts arise about the suitability of the coating for your surface, we will gladly test your surface samples.

Product information:

MARISEAL•DETAIL		
Description	One component, polyurethane-based, liquid membrane, reinforced with synthetic fibers	
Packaging	supplied in 6 kg pails	
Properties	Color	Grey, Black
	Density	1.32 g/cm ³
	Hardness (Shore A scale)	70
	Viscosity	Thixotropic
	Elongation at Break	>250%
	Tensile strength	>4 N/mm ²
	Rain stability time (20°C)	3-4 Hours
	Light pedestrian traffic	12-18 Hours
	Final Curing time	7 Days

MARISEAL•DETAIL PRIMER		
Description	One-component, quick drying, polyurethane-based primer	
Packaging	supplied in 1kg pails	
Properties	Color	Transparent
	Density	1.0 g/cm ³
	Hardness Shore A	>95
	Adhesion (Concrete)	>1.5 N/mm ²
	Touch dry (20°C)	1-2 Hours

Safety measures: contains isocyanates. See information supplied by the manufacturer. Please study the Safety Data sheet.